

l'airpurTM VAC



TECHNICAL DATA	ALAIP01A	ALAIP02A	ALAIP03A
Motor	Bypass	Bypass	Bypass (2x)
Airwatts	540	605	1,160 AW
Decibels	67	68	70 dB
Air flow (CFM)	118	131	2 x 124 CFM
Water lift H2O (in)	123.5	128	134"
MAX amps	13.4	14	14.5 A
Voltage	120 V	120 V	240 V
Principle	Hybrid	Hybrid	Hybrid
Filtration	Bag or self-cleaning filter	Bag or self-cleaning filter	Bag or self-cleaning filter
Bag capacity (gal US)	4.5 gal US	4.5 gal US	5 gal US
Canister capacity (gal US)	3.95 gal US	3.95 gal US	5.3 gal US
Double intake	✓	✓	✓
Side Utility inlet	✓	✓	✓
Warranty	10 years	10 years	10 years
CLEANING SURFACE[†]	Up to 4000 sq. ft.	Up to 6000 sq. ft.	Up to 20,000 sq. ft.

* FOR INFORMATIONAL PURPOSES ONLY. ALWAYS CONSULT YOUR CENTRAL VACUUM SPECIALIST FOR APPROPRIATE SIZED UNIT.

ARLENCO DISTRIBUTION INC.

Corona
Albuquerque
Boise
Spokane
Salt Lake City
Portland
Las Vegas
Dallas

ARLENCO
DISTRIBUTION, INC.